



Countrywide Heating
and Cooling Ltd

Hire • Sales • Service

www.countrywideheating.com

Freefone 0800 195 2160

Electric Heaters



Fan Heater

Also available in 2kw or 3kw

- Flat position fan heater
- Cool fan setting
- Ideal for summer use
- Adjustable thermostat, with frost protection
- Safety overheat cut-out
- Cord storage
- Rotary switch controls

FH550

Low Convector

- Adjustable thermostat
- Variable heat control
- Free standing unit
- Safety overheat cut-out
- Tube heating element
- Max power consumption: 2kw



Convector Heater

also available with turbo fan

- Programmable 24hr timer
- 3 heat settings
- Adjustable thermostat control
- Safety overheat cut-out
- Free standing or wall mountable



CW95 20kw Heater

- Industrial and commercial use
- Factories, foundries, warehouses and manufacturing
- 3 phase (415 volt)
- 3 heat settings
- Overheat Protection



Oil Filled Radiator 7, 9 or 11 Fin

- Thermostatically controlled
- 24hr timer
- 1.5kw - 3kw

CW240 Quartz Heater

Also available in 110v

- Construction, offices, exhibitions halls, public buildings, schools, canteens and leisure centres
- Highly portable
- Instantaneous heat
- Flexible and simple to use
- For indoor use only



Gas Heaters



CW125/280

Gas Heater

- Industrial and commercial use
- Factories, foundries, warehouses and manufacturing
- Adjustable output
- Dual voltage section
- Flame failure and overheat protection
- Fan only option
- 38kw (130,000btu)
- 82kw (281,000btu)

Catalytic Cabinet Heater

- Industrial and commercial use
- Ideal for use in small, well ventilated areas where spot heating is required
- Adjustable output
- Flame failure protection
- Uses 12kg butane gas bottles



Direct Heaters

GE55/GE90

Direct Fired

- Industrial and commercial use
- Factories, foundries, warehouses and agriculture
- Flexible and simple to use
- Optional thermostat
- For indoor use only
- Overheat protection
- No warm up period required



Indirect Heaters



EC40/EC70

Indirect Fired

- Industrial and commercial use
- Sites, factories, garages, warehouses, exhibition halls, clothing and food manufacturing.
- Delivers large volumes of clean, dry air through long duct runs
- Thermostatically controlled
- Can be sited indoors or outdoors
- Integral fuel tank (can be used with separate 205ltr fuel drum)
- 37kw (126,000btu) / 68kw (232,000btu)

